

FORTE 117



TECHNICAL SPECS

- 32° F to 44.6° F / 0° C to 7° C
- 4.86 kWh / 24 hr
- LED perimetral lighting
- 209.43 lbs / 95 kg
- 480 liters / 17 ft³
- 378 bottles of 10.14 oz / 330 ml
223 bottles of 16.9 oz / 500 ml
- 302 cans of 22.9 oz / 680 ml
540 cans of 12 oz / 355 ml
- 51 units 40' container
60 units 48' box

- Compressor:** Last generation
- Fan motors:** Shaded pole *Optional electronic of high efficiency
- Controller:** Electronic controller with energy saving mode
- Voltage:** 110V ± 10%
- Shelves:** 4 shelves
- Interior:** Stainless steel 304
- Exterior:** Stainless steel T-430
- Foaming:** Polyurethane with cyclopentane gas as foaming agent, 100% CFC-free and non-toxic
- Door:** Duo-vent tempered glass door 0.11 in / 3mm thick and steel frame. Welded corners. Handle embedded in the door frame. Magnetic PVC gasket. Stainless steel T-430 hinges. Available in solid door version.
- Base:** Galvanized sheet structure, skid rail in high density PE, stainless steel T-430 Louver



DIMENSIONS	EXTERIOR	INTERIOR
(A) WIDTH	736 mm	624 mm
(B) DEPTH	681 mm	492 mm
(C) HEIGHT	1217 mm	1564 mm