











FORTE V22



TECHNICAL SPECS

-  32° F to 44.6° F / 0° C to 7° C
-  7.1 kWh / 24 hr
-  LED perimetral lighting
-  244.7 lbs / 111 kg
-  518.5 liters / 22 ft³
-  378 bottles of 10.14 oz / 330 ml
223 bottles of 16.9 oz / 500 ml
-  302 cans of 22.9 oz / 680 ml
540 cans of 12 oz / 355 ml
-  48 units 40' container
57 units 48' box

- Compressor:** Last generation
- Fan motors:** Shaded pole *Optional electronic of high efficiency
- Controller:** Electronic controller with energy saving mode
- Voltage:** 110V ± 10%
- Shelves:** 4 shelves
- Interior:** Prepainted white steel sheet
- Exterior:** Prepainted black steel sheet
- Foaming:** Polyurethane foam 1.5 in / 38.1 mm thick, 100% CFC-free and non-toxic
- Door:** Duo-vent tempered glass door 0.11 in / 3mm thick and PVC frame. Welded corners. Plastic knobs embedded in the door frame. Magnetic PVC gasket. Steel hinges with electrostatic powder paint
- Base:** Galvanized sheet structure, skid rail (PP), plastic Louver



DIMENSIONS	EXTERIOR	INTERIOR
Ⓐ Width	700 mm	624 mm
Ⓑ Depth	792 mm	649 mm
Ⓒ Height	2011 mm	1564 mm