












FORTE V5



TECHNICAL SPECS

-  32° F to 44.6° F / 0° C to 7° C
-  2.86 kWh / 24 hr
-  LED perimetral lighting
-  143.3 lbs / 65 kg
-  142.7 liters / 5 ft³
-  123 bottles of 10.14 oz / 330 ml
63 bottles of 16.9 oz / 500 ml
-  88 cans of 22.9 oz / 680 ml
135 cans of 12 oz / 355 ml
-  80 units in 40' container
72 units in 48' box

- Compressor:** Last generation
- Fan motors:** Shaded pole *Optional electronic of high efficiency
- Controller:** Electronic controller with energy saving mode
- Voltage:** 110V ± 10%
- Shelves:** 2 shelves
- Interior:** Prepainted white steel sheet interior
- Exterior:** Prepainted black steel sheet exterior
- Foaming:** Polyurethane foam 1.5 in / 38.1 mm thick, 100% CFC-free and non-toxic.
- Door:** Duo-vent tempered glass door 0.11 in / 3mm thick and PVC frame. Welded corners. Plastic knobs embedded in the door frame. Magnetic PVC gasket. Steel hinges with electrostatic powder paint.
- Base:** Galvanized sheet structure, skid rail (PP), plastic Louver



DIMENSIONS	EXTERIOR	INTERIOR
(A) WIDTH	545 mm	445 mm
(B) DEPTH	515 mm	388 mm
(C) HEIGHT	1310 mm	830 mm